



鄭州登峰熔料有限公司

Zhengzhou Dengfeng Smelting Materials Co., Ltd

Dengfeng Smelting Materials produces high-purity calcium aluminate cement with Al_2O_3 content levels of 50%, 60%, 70%, and 80%. It is free from any organic additives, allowing for complete design flexibility and eliminating potential chemical incompatibility. This product is widely used in the refractory industry.

The 50% content calcium aluminate cement (CA50) is available in three types:

1. Aluminate Cement For Refractories Ca50 Series

- CA50-II(G6), CA50-III(G7), CA50(N), CA50-IV(G9), CA50 (Fused)

2. Chemical Building Materials Calcium Aluminate Cement Series:

- CA50-J6, CA50-J7, CA50-J9, CA50-JN, CA50-J Fused

3. Special Aluminate Cement For Cast Pipes (PI-ZY)

CA50 is a well-established product series. Our process allows us to produce CA50 cement in five different strength ranges, providing opportunities for developing products with consistent and predictable characteristics. The CA50 series calcium aluminate cement has main mineral phases of calcium aluminate (CA) and dicalcium aluminate (CA₂), which is an essential binder in the production of high, medium, and low-grade monolithic refractories. Due to its excellent physical and chemical properties, it is widely used in metallurgy, building materials, petrochemical, power plants, boilers, and other industrial furnace industries.

The chemical building materials calcium aluminate cement series has more stringent control over various parameters to achieve better product performance. The combination of calcium aluminate cement and Portland cement can utilize the early strength characteristics of the calcium aluminate cement while retaining the later strength and durability of Portland cement. The reaction of calcium aluminate cement with Portland cement and gypsum can rapidly form calcium sulfoaluminate, which, through appropriate proportions, can form quick-hardening, shrinkage-compensating, and other properties. Combined with various chemical additives, this cement is widely used in the preparation of various commercial mortars, such as tile adhesives, thin-set adhesives, self-leveling floor materials, sealants, waterproofing materials, fast-setting mortars, repair mortars, bonding mortars, and pouring mortars.

Special Aluminate Cement For Cast Pipes(PI-ZY) is a product developed by Dengfeng Smelting Materials specifically for centrifugal casting of sewage pipes with steam curing processes. The mortar made with this cement has excellent resistance to sewage corrosion, high flowability, and long-lasting flow time. It meets the requirements for good workability and non-clogging during the centrifugal forming process of pipes. Additionally, its broad gray-to-sand ratio adaptability offers possibilities for enhancing efficiency for users.

The Pure Calcium Aluminate Cement Series with 60%, 70%, and 80% Al_2O_3 content includes three types:

1. CA65P, CA68

2. NA71, CA70, CA75

3. CA80

In the refractory industry, pure calcium aluminate cement is primarily used as a binder for preparing refractory castables with temperatures ranging from 1500 ° C to 1800 ° C, and even exceeding 1800 ° C, especially for low-cement and ultra-low cement castables.

Pure Aluminate Cement Series For Refractory Materials

60% 70% 80% Al₂O₃ Cement - Product Data

	CA65P	CA68	NA71	CA70	CA75	CA80
Refractoriness(°C)	1610-1650	1610-1650	1650-1690	1650-1690	1710-1750	1780-1820
Al ₂ O ₃ (%)	≥64	65-68	68-70	68-72	≥73	≥77
CaO (%)	≤35.0	31.0-33.0	28.5-30.0	≤30.0	≤25.0	≤20.0
SiO ₂ (%)	≤1.0	≤0.7	≤0.7	≤0.7	≤0.7	≤0.5
Fe ₂ O ₃ (%)	≤0.5	≤0.4	≤0.4	≤0.4	≤0.4	≤0.4
Alkali content (%)	≤0.4	≤0.4	≤0.4	≤0.4	≤0.4	≤0.4
Specific Surface of Cement-Blaine Method (m ² /kg)	≥450	≥450	≥400	≥500	≥500	≥550
Initial Setting Time(min)	≥30	≥30	≥90	≥30	≥30	≥30
Final Setting Time(min)	≤360	≤360	≤360	≤360	≤360	≤360
6-8h Flexural (MPa)	-	-	≥3.0	-	-	-
24h Flexural (MPa)	≥9.0	≥9.0	≥8.0	≥8.0	≥6.0	≥5.0
72h Flexural (MPa)	≥11.0	≥11.0	≥10.0	≥10.0	≥7.0	≥6.0
6-8h Compressive (MPa)	-	-	≥15.0	-	-	-
24h Compressive (MPa)	≥60.0	≥60.0	≥50.0	≥50.0	≥40.0	≥35.0
72h Compressive (MPa)	≥70.0	≥70.0	≥60.0	≥60.0	≥50.0	≥45.0

Pure calcium aluminate cement binders for refractory materials are primarily used to formulate refractory castables for temperatures ranging from 1500-1800°C, and even above 1800°C, particularly for low-cement and ultra-low-cement castables.

CA65P, CA68

- With a high content of CA minerals, it has good early strength and high strength.
- Formulation of ultra-high strength, wear-resistant, low-cement refractory castables, etc.
- Production of ultra-high strength refractory precast blocks.

NA71

- Primary mineral composition of CA with secondary CA₂, featuring an optimal CA/CA₂ ratio, moderate specific surface area, excellent rheology, stable performance, and strong resistance to reducing atmospheres.
- Applications: Ideal for formulating high-purity, low-cement refractory castables and high-purity refractory castables.
- Uses in high-performance refractory pre-cast blocks, such as electric furnace covers, iron runner channels, and slotted bricks.
- Construction mortar formulations: Suitable for colored floor mortar, facing mortar, grout, and other building mortars.

CA70

- Mainly composed of CA minerals with CA₂ as a secondary component, it has an optimal ratio of CA to CA₂, a higher specific surface area, higher strength, good workability, stable performance, and strong resistance to reducing atmospheres.
- Suitable for water-rich, medium-cement, low-cement, and ultra-low-cement castables, for use as pumpable and sprayable materials, self-flowing castables, ramming mixes, and troweling mixes.
- Production of high-performance refractory precast blocks such as electric furnace roofs and tapholes.

CA75

- The product performance falls between CA70 and CA80, with a wide range of adaptability.
- Suitable for water-rich, medium-cement, low-cement, and ultra-low-cement castables.
- Production of high-performance refractory precast blocks such as electric furnace covers and tapholes.

CA80

- CA80 has a low impurity content, high purity, stable performance, higher refractoriness, and higher high-temperature resistance.
- High-performance, high-purity, low-cement, ultra-low-cement castables.
- Production of linings for steel ladles, electric furnace covers, tapholes, etc.

The cement production process at Dengfeng Smelting Materials is designed to achieve maximum consistency. Through precise and stringent control, we can accurately ensure the refractory quality and performance of the cement. This approach significantly reduces response times and enhances production flexibility, allowing us to deliver superior service.

Cement Testing and Quality Control

Dengfeng Smelting Materials' aluminate cement is engineered to actively meet customer requirements. Key qualities of high-performance cement include setting consistency, flowability, strength, particle size distribution, and precise chemical composition. Our quality control system is meticulously designed to ensure consistent product quality, enhancing the reliability and performance of customers' applications.

Our cement undergoes rigorous testing to meet standards, including flowability, setting time, and strength assessments based on the Chinese GB201/T2015 standard with standardized sand. Tests include specific surface area, initial and final setting times, flexural and compressive strength. Chemical composition is verified through X-ray fluorescence spectroscopy (XRF).

Packaging Options

- Bulk bags
- Small bags

Shelf Life and Storage

To ensure longevity, all Dengfeng Smelting aluminate cements should be stored in original, sealed packaging under dry conditions. Experience shows that even after prolonged storage, performance remains unaffected if the product is kept in optimal conditions. However, direct sunlight may degrade plastic packaging over time, necessitating additional protection to avoid UV exposure. Shrink-wrap should remain intact until use, as removing it may reduce the cement's shelf life.



This brochure provides general guidance on the basic properties and characteristics of various Dengfeng Smelting Materials products (hereinafter referred to as "Product Information") for potential customers. Dengfeng Smelting Materials makes no guarantee or warranty as to the accuracy or completeness of the Product Information in this brochure.

- Nothing in this brochure should be interpreted as providing any express or implied warranties or obligations by Dengfeng Smelting Materials regarding the Product Information or its use, including but not limited to warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property rights.
- Each user of Dengfeng Smelting Materials products is responsible for determining the appropriate application and suitability of the Product Information within their specific operations. Users should exercise due caution when considering product data sheets, Product Information, and any other technical information provided by Dengfeng Smelting Materials, including usage conditions, warnings, and other advisories.
- Dengfeng Smelting Materials reserves the right to modify Product Information at its sole discretion from time to time without prior notice.
- Our company is committed to bearing legal responsibility for any personal injury or property damage resulting from product defects. Users should carefully review the product instructions and safety guidelines prior to use.

Headquarters

Consultation Phone:

0371-62976006

Sales Phone:

0371-62976009, 62977009

Address:

Xuanhua Town, Dengfeng City, Zhengzhou, Henan Province, China

Global Business Team

Manager Zhang: +86 13608687776

Manager Sun: +86 13949024780

Email: info@dfritglobal.com

Address:

Block A, Greenland Window,
Zhengdong New District, Zhengzhou,
Henan Province, China